





中国认可 国际互认 检测 TESTING CNAS L0599

Test Report SL52025246081401TX Date: June 08,2020 Page 1 of 10

CONNEXIONS TECHNOLOGY (DONG GUAN) LTD NO. 6, SHENBAO ROAD, QISHI TOWN, DONGGUAN CITY, GUANGDONG PROVINCE

The following sample(s) was/were submitted and identified on behalf of the client as:

Sample Description : (A)Face mask

Style No. : CTPL-0020

Composition : (A)Non-woven fabric, melt-blown fabric, hot air cotton

Sample Color : (A)WHITE

Manufacturer : CONNEXIONS TECHNOLOGY (DONG GUAN) LTD

Country of Destination : Global

Supplier : CONNEXIONS TECHNOLOGY (DONG GUAN) LTD

Test Performed : Selected test(s) as requested by applicant

Sample Receiving Date : Apr 28, 2020

Testing Period : Apr 29, 2020 - Jun 08, 2020

Test Result(s) : Unless otherwise stated the results shown in this test report refer only to the

sample(s) tested, for further details, please refer to the following page(s).

Conclusion:

Sample No.	Recommendation Level		
(A)	FFP2 NR		

Signed for and on behalf of SGS-CSTC Standards Technical Services (Shanghai) Co., Ltd Testing Center

Sara Guo (Account Executive)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overload, available on request or accessible at http://www.ags.com/ser/General-Conditions/Terms-e-Documents, subject to Terms and Conditions/Terms-e-Documents at http://www.ags.com/ser/Terms-and-Conditions/Terms-e-Documents.ags.com/ser/Terms-and-Conditions/Terms-e-Documents.ags.com/ser/Terms-and-Conditions/Terms-e-Documents.ags.com/ser/Terms-and-Conditions/Terms-e-Document-approximate the distance of service to the implication of sability, indemnification and jurisdiction issues defined herein. Any holder of this document advanced that information contained herein reflects the Company's flucting at the time of its intervention only and within the limits of Clients instructions, if any. The Company sole responsibility to bits Client and this document does not accessible to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company, Any unsurfavorized alternation, longery or fluidification of the containt or appearance of this document is unfavoral and effenders may be protected to the fullest action of the law. Unless otherwise stated the regulate shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

J^{*}Building,No.888,Yehan Road, Autu, Dearld Shanghai, Dinne 200233 中國 - 上海 - 保汇区宣山路889号3号像 部第: 200233 1 (96-21) 61402666 1 (96-21) 61402666

f (86-21) 64958763 f (86-21) 64958763



SL52025246081401TX

Page 2 of 10

Test Result

Respiratory Protective Devices — Filtering Half Masks to Protect against Particles — Requirements, Testing, Marking

Date: June 08,2020

(EN 149:2001+A1:2009)

Clause 7.4 Packaging

(EN 149:2001+A1:2009 Clause 8.2)

Test Requirement	Results	Comment
Particle filtering half masks shall be offered for sale packaged in such a way that they are protected against mechanical damage and contamination	Comply	Pass
before use.		

Clause 7.5 Material

(EN 149:2001+A1:2009, Clause 8.2 & 8.3.1 & 8.3.2)

Test Requirement	Results	Comment
Materials used shall be suitable to withstand handling and wear over the period for which the particle filtering half mask is designed to be used.	Comply	
After undergoing the conditioning described in 8.3.1 none of the particle filtering half masks shall have suffered mechanical failure of the facepiece or straps.	Comply	Pass
When conditioned in accordance with 8.3.1 and 8.3.2 the particle filtering half mask shall not collapse.	Comply	
Any material from the filter media released by the air flow through the filter shall not constitute a hazard or nuisance for the wearer.	Comply	

Clause 7.6 Cleaning and Disinfecting

(EN 149:2001+A1:2009, Clause 8.4 & 8.5 & 8.11)

Test Requirement	Results	Comment
If the particle filtering half mask is designed to be re-usable, the materials used shall withstand the cleaning and disinfecting agents and procedures to be specified by the manufacturer. With reference to 7.9.2, after cleaning and disinfecting the re-usable particle filtering half mask shall satisfy the penetration requirement of the relevant class.	Not applicable (Not designed to be re-usable)	N.A.

Clause 7.7 Practical Performance

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The particle filtering half mask shall undergo practical performance tests under realistic conditions. These general tests serve the purpose of checking the equipment for imperfections that cannot be determined by the tests described elsewhere in this standard.	No imperfections	Pass



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request or accessible at Into Newwass, coming Retris-into-Conditions, agas and, for electronic format documents, asoliced to Terms and Conditions Terms—e-Occurrents at http://www.ass.coming/Terms—eitd-Conditions Terms—e-Occurrents at http://www.ass.coming/Terms—eitd-Conditions Terms—e-Occurrents at Assertion is drawn to the destination of liability, indemnification and printed Sens issues defined thereis. Any fooliar of this document assertion is drawn to the destination contained become reflects the Company's fluctings at the time of its intervention only and within the lerits of Clern's instructions, if any. The Company's soic responsibility is to its Clern's and this document cannot be reproduced accept in full, without prior written approved of the Company. Any unsurfacing alleration, lergery or fluidification of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this later report terior only to be company. Any unsurfacing an entained for 35 days only.

Appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this later report effect only to the earthful process.

3"Building,No.389,Yeher: Road,Xuhui Dietrict Shanghai,Chine 2002/33 中國 - 上海 - 徐汇区宣山路889号3号楼 - 邮箱: 200233

1 (86-21) 61402666

1 (86-21) 64958763



SL52025246081401TX

Date: June 08,2020

Page 3 of 10

Clause 7.8 Finish of Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
Parts of the device likely to come into contact with the wearer shall have no sharp edges or burrs.	No sharp edges or burrs	Pass

Clause 7.9.1 Total Inward Leakage

(EN 149:2001+A1:2009, Clause 8.5)

Test Requirement	Results	Comment
The total inward leakage consists of three components: face seal leakage, exhalation value leakage(if exhalation value fitted) and filter penetration. For particle filtering half masks fitted in accordance with the manufacturer's information, at least 46 out of the 50 individual exercise results (i.e. 10 subjects x 5 exercises) for total inward leakage shall be not greater than: 25% for FFP1, 11% for FFP2, 5% for FFP3	Detail refer to Appendix 1	Meet FFP1, Meet FFP2
and, in addition, at least 8 out of the 10 individual wearer arithmetic means for the total inward leakage shall be not greater than: 22% for FFP1, 8% for FFP2, 2% for FFP3		

Appendix 1: Summarization of Test Data

Inward Leakage Test Data

ill Wald Leakage Test Data								
Subject	Sample	Condition	Walk(%)	Head	Head	Talk(%)	Walk(%)	Mean(%)
	No.			Side/side(%)	up/down(%)			
Zhou	1	A.R.	6.11	5.08	7.73	5.47	6.33	6.14
Luo	2	A.R.	7.84	6.74	7.17	5.90	8.26	7.18
Lu	3	A.R.	6.44	4.86	6.48	6.18	7.10	6.21
Wang	4	A.R.	5.86	5.60	4.78	5.41	4.82	5.29
Bao	5	A.R.	8.29	8.66	7.51	6.82	5.91	7.44
Ding	6	T.C.	5.59	4.76	5.54	4.97	5.85	5.34
Li	7	T.C.	8.25	7.75	6.81	7.63	8.40	7.77
Chen	8	T.C.	5.45	5.05	5.98	5.58	5.35	5.48
Song	9	T.C.	5.60	6.81	5.64	6.70	6.99	6.35
Ye	10	T.C.	8.33	7.88	8.11	6.80	8.22	7.87

Facial Dimension(mm)

Subject	Face length	Face Width	Face Depth	Mouth Width
Chen	125	150	120	58
Lu	115	132	107	48
Zhou	115	135	106	52
Li	125	130	107	46
Luo	125	136	100	43
Zheng	128	140	112	55
Wang	120	147	103	48
Song	120	140	100	50
Bao	130	134	104	50



Unless attention agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request or accessible at Into Neww.scs. coming/Estas-and-Conditions, aggs and, for electronic format documents, asobject to Teams and Conditions Teams—Cocuments at http://www.scs.coming/Estas-and-Conditions/Teams—Cocuments—Co

3"Building, No. 889, Yehen Road, Yuhui Dietrich Shanghai, Chine 2002/33 中國 - 上海 - 徐汇区宣山路859号3号楼 - 邮编: 200233

1 (86-21) 61402666

1 (86-21) 64958763



Test Re	port SL520	25246081401TX	Date: June 08,2020	Page 4 of 10
Ding	134	150	110	52
Liu	120	135	117	50
Ye	126	137	105	52

Clause 7.9.2 Penetration of Filter Material

(EN 149:2001+A1:2009, Clause 8.11 & EN 13274-7:2019)

		Test Requirement		Results	Comment	
		of the filter of the particle filte	the			
1040	requirements of the following table. Classifica Maximum penetration of test aerosol					
	tion	Sodium chloride test 95	Paraffin oil test 95 l/min			
		l/min			Detail refer to	Meet FFP1,
		%	%		Appendix 2	Meet FFP2
		max.	max.			
	FFP1	20	20			
	FFP2	6	6			
	FFP3	1	1			

Appendix 2: Summarization of Test Data

Penetration of filter material

Aerosol	Condition	Sample No.	Penetration (%)
		1	0.117
	As received	2	0.126
		3	0.119
		4	0.145
Sodium chloride test	Simulated wearing treatment	5	0.190
		6	0.175
	Mark a size I store with a Tanan and and	7	0.412
	Mechanical strength +Temperature conditioned	8	0.317
	conditioned	9	0.396
	As received	10	0.201
		11	0.306
		12	0.287
		13	0.279
Paraffin oil test	Simulated wearing treatment	14	0.314
	_	15	0.336
	Mark a size I store with a Tanan and and	16	3.674
	Mechanical strength +Temperature	17	4.124
	conditioned	18	4.176
	Flow conditioning: Single fil	ter: 95.0 L/min	



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overfeet, available on request or accessible at http://www.scs.com/inn/Terms-and-Conditions

3"Building, No. 889, Yehen Road, Kuhui Dietrich Shanghai, Chine 2002/33 中國 - 上海 - 徐汇区宣山路859号3号楼 - 邮编: 200233

1 (86-21) 61402666

f (86-21) 64958763



SL52025246081401TX

Page 5 of 10

Clause 7.10 Compatibility with Skin

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
Materials that may come into contact with the wearer's skin shall not be known to be likely to cause irritation or any other adverse effect to health.	No irritation or any other adverse	Pass
known to be likely to educe initiation of any other deverse effect to ficulti.	effect to health	1 433

Date: June 08,2020

Clause 7.11 Flammability

(EN 149:2001+A1:2009, Clause 8.6)

Test Requirement	Results	Comment
The material used shall not present a danger for the wearer and shall not be of highly flammable nature When tested, the particle filtering half mask shall not burn or not to continue to burn for more than 5 s after removal from the flame.	Detail refer to Appendix 3	Pass

Appendix 3: Summarization of Test Data

Flammability

Condition	Sample No.	Result
As received	1	NIL
AS received	2	NIL
Tomporature conditioned	3	NIL
Temperature conditioned	4	NIL

Clause 7.12 Carbon Dioxide Content of The Inhalation Air

(EN 149:2001+A1:2009, Clause 8.7)

Test Requirement	Results	Comment
The carbon dioxide content of the inhalation air (dead space) shall not	Detail refer to	Pass
exceed an average of 1,0 % (by volume)	Appendix 4	1 033

Appendix 4: Summarization of Test Data

Carbon Dioxide Content of The Inhalation Air

Condition	Sample No.	Result(%)				
	1	0.4875				
As received	2	0.4862	Mean value:0.49			
	3	0.4869				



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at Into Neww.scs. content Estate. Conditions args and, for electronic format documents at http://www.scs.com/ani/format/scs/conditions/ferral-e-Occuments at http://www.scs.com/ani/ferral-e-Occuments at http://www.scs.com/ani/ferral-e-Occuments.acc.
Attention to drawn to the destination of liability, indemnification and jurisdiction issues defined thereis. Any foolder of this document as advised that information contained however reflects the Company's findings at the time of its intervention only and within the lerits of Cleant's instructions, if any. The Company's soic responsibility is to its Cleant and this document does not expended accept in full, without prior written approved of the Company. Any unsurfacing alleration, lergery or furthingshow of the content of appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this lest report refer only to the earthful of the lawful such samples) are retained for 35 days only.

According to the According account.

3"Building,No.889, Yeher: Road, Yuhui Dietrich Shanghai, Chine 2002/33 中國 - 上海 - 徐汇区宣山路859号3号楼 部第: 200233

1 (86-21) 61402666

1 (86-21) 64958763



SL52025246081401TX

Date: June 08,2020 Page 6 of 10

Clause 7.13 Head Harness

(EN 149:2001+A1:2009, Clause 8.4 & 8.5)

Test Requirement	Results	Comment
The head harness shall be designed so that the particle filtering half mask can be donned and removed easily.	Comply	
The head harness shall be adjustable or self-adjusting and shall be sufficiently robust to hold the particle filtering half mask firmly in position and be capable of maintaining total inward leakage requirements for the device.	Comply	Pass

Clause 7.14 Field of Vision

(EN 149:2001+A1:2009, Clause 8.4)

Test Requirement	Results	Comment
The field of vision is acceptable if determined so in practical performance tests.	Comply	Pass

Clause 7.15 Exhalation Valve(s)

(EN 149:2001+A1:2009, Clause 8.2 & 8.9.1 & 8.3.4 & 8.8)

Test Requirement	Results	Comment
(a) A particle filtering half mask may have one or more exhalation valve(s), which shall function correctly in all orientations.	Not applicable due to No exhalation valve	
(b) If an exhalation valve is provided it shall be protected against or be resistant to dirt and mechanical damage and may be shrouded or may include any other device that may be necessary for the particle filtering half mask to comply with 7.9.	Not applicable due to No exhalation valve	N.A.
(c) Exhalation valve(s), if fitted, shall continue to operate correctly after a continuous exhalation flow of 300 l/min over a period of 30 s.	Not applicable due to No exhalation valve	
(d) When the exhalation valve housing is attached to the faceblank, it shall withstand axially a tensile force of 10N applied for 10 s.	Not applicable due to No exhalation valve	



Unless attention agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overlead, available on request or accessible at Into Neww.scs. coming/Estas-and-Conditions, aggs and, for electronic format documents, asobject to Teams and Conditions Teams—Cocuments at http://www.scs.coming/Estas-and-Conditions/Teams—Cocuments—Co

3"Building,No.389,Yeher: Road,Xuhui Dietrict Shanghai,Chine 2002/33 中國 - 上海 - 保汇区室山路889号3号楼 部第: 200233

1 (86-21) 61402666

f (86-21) 64958763



SL52025246081401TX

Date: June 08,2020

Page 7 of 10

Clause 7.16 Breathing Resistance

(EN 149:2001+A1:2009, Clause 8.9)

	Tes	Results	Comment			
The penetration requirements of						
Classification	Maximu	um permitted resista		Datail nafanta	Meet FFP1,	
	Inh	nalation	Exhalation		Detail refer to	Meet FFP2, Meet FFP3
	30 l/min	95 l/min	160 l/min		Appendix 5	Meet FFP3
FFP1	0.6	2.1	3.0			
FFP2	0.7	2.4	3.0			
FFP3	1.0	3.0	3.0			

Appendix 5: Summarization of Test Data

Breathing resistance (mbar)

					1					2					3				
	Flow rate(l	/min)	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е		
As received	Inhalation	30	0.2	0.2	0.2	0.2	0.3	0.3	0.3	0.2	0.2	0.2	0.2	0.2	0.2	0.3	02		
	Inhalation	95	0.8	0.7	0.8	0.8	0.8	0.7	0.8	0.8	0.8	0.8	0.7	0.8	0.9	0.8	0.8		
	Exhalation	160	1.5	1.6	1.5	1.6	1.7	1.6	1.6	1.6	1.6	1.5	1.6	1.6	1.6	1.6	1.7		
							4					5					6		
Simulated	Flow rate(l	min)	Α	В	С	D	Е	Α	В	С	D	Е	Α	В	С	D	Е		
wearing	Inhalation	30	0.3	0.3	0.2	0.2	0.3	0.3	0.2	0.3	0.3	0.3	0.2	0.3	0.2	0.3	0.3		
treatment	IIIIaiation	95	0.9	0.8	0.8	0.7	0.8	0.8	0.8	0.9	0.8	0.8	0.9	0.7	0.8	0.8	0.9		
	Exhalation	160	1.6	1.6	1.4	1.5	1.6	1.6	1.5	1.5	1.4	1.6	1.6	1.6	1.6	1.5	1.5		
	El	/ · - \			7					8			9						
	Flow rate(l/	min)	Α	В	С	D	Е	Α	В	С	ם	Е	Α	В	С	D	Е		
Temperature	Inhalation	30	0.2	0.2	0.2	0.3	0.2	0.2	0.2	0.3	0.2	0.2	0.2	0.2	0.2	0.3	0.2		
conditioned Inhalation	95	0.7	0.7	0.6	0.7	0.7	0.6	0.6	0.7	0.6	0.6	0.6	0.6	0.6	0.7	0.7			
	Exhalation	160	1.3	1.3	1.4	1.3	1.4	1.3	1.3	1.3	1.4	1.3	1.3	1.4	1.4	1.3	1.4		

A: facing directly ahead; B: facing vertically upwards; C: facing vertically downwards; D: lying on the left side; E: lying on the right side



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overloaf, available on request or accessible at Into Newwass, coming Rems-end-Conditions agas and, for electronic format documents, as the Into Newwass, contain Rems-end-Conditions are interested to the rems and Conditions for its intermediation. Attention is drawn to the destination of liability, indemnification and printed Sent Industrial Research Conditions for the Section of Section 1 and the Section of Section 1 and the Section of Section 1 and Section

3"Building,No.889, Yeher: Road, Yuhui Dietrich Shanghai, Chine 2002/33 中國 - 上海 - 徐汇区宣山路859号3号楼 部第: 200233

1 (86-21) 61402666

f (86-21) 64958763



SL52025246081401TX

Date: June 08,2020 Page 8 of 10

Clause 7.17 Clogging

(EN 149:2001+A1:2009, Clause 8.9 & 8.10)

	Test Requirement	Results	Comment
Valved particle fill After clogging the FFP1: 4 mbar, FI The exhalation re flow. Valveless particle After clogging the	eathing resistance tering half masks: e inhalation resistances shall not FP2: 5 mbar, FFP3: 7 mbar at 95 esistance shall not exceed 3 mb e filtering half masks: e inhalation and exhalation resis FP2: 4 mbar, FFP3: 5 mbar at 95	Optional for single shift device only	N.A.
All types (valved	enetration of filter material If and valveless) of particle filter g requirement shall also meet th Maximum penetration Sodium chloride test 95 l/min % max. 20 6 1	Optional for single shift device only	N.A.

Clause 7.18 Demountable Parts

(EN 149:2001+A1:2009, Clause 8.2)

Test Requirement	Results	Comment
All demountable parts (if fitted) shall be readily connected and secured,	No demountable	N.A.
where possible by hand	parts	IN.A.

Test	Uncertainty
Total inward leakage	3.4%
Penetration of filter material	4.8%
Carbon dioxide content of the inhalation air	3.9%
Breathing resistance (30L/min)	5.9%
Breathing resistance (95L/min)	4.9%
Breathing resistance (160L/min)	4.3%



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overfeet, available on request or accessible at http://www.scs.com/inn/Terms-and-Conditions

2"Building No. 889, Yehen Road, Yuhui Dietrich Shenghai, Chine 2002/33 中國 - 上海 - 徐汇区宣山路859号3号楼 - 邮编: 200233

1 (86-21) 61402666


f (86-21) 64958763



SL52025246081401TX

Date: June 08,2020 Page 9 of 10

Sample Photo





Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overfeet, available on request or accessible at http://www.scs.com/inn/Terms-and-Conditions


3"Building, No. 889, Yehen Road, Kuhui Dietrich Shanghai, Chine 2002/33 中國 - 上海 - 徐汇区宣山路859号3号楼 - 邮编: 200233

1 (86-21) 61402666

t (96-21) 61402686 F (86-21) 64958763 f (86-21) 64958763



SL52025246081401TX Date: June 08,2020





End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overfeet, available on request or accessible at http://www.scs.com/inn/Terms-and-Conditions

2"Building No. 889, Yehen Road, Yuhui Dietrich Shenghai, Chine 2002/33 中國 - 上海 - 徐汇区宣山路859号3号楼 - 邮编: 200233

1 (86-21) 61402666

t (96-21) 61402686 F (86-21) 64958763 f (86-21) 64958763